

**General Information:**

Asphalt-Tac is an asphalt emulsion tack coat that meets DOT standards for SS-1h. Consult specific product and application specifications before use.

**Mix Design:**

Use full strength, do not dilute. Stir well before use.

**Application:**

As a tack coat to asphalt overlays or under patches, apply .1 gal./sy to the prepared surface.

**Product Limitations:**

1. Do not allow to freeze.
2. Container must be closed when not in use.
3. Stir well before using.
4. Do not apply when rain is expected within 8 hours or when ground and air temperature are or will be 50°F or lower before product is dry.

**For Commercial Use Only**

# ASPHALT-TAC

## Tack Coat

**BREWPRO**<sup>®</sup>  
PAVEMENT PRODUCTS

*Professional Grade*

NET CONTENTS: 5 US GAL / 18.9 L

**Warning:**

May cause eye and skin irritation. Use under well-ventilated conditions.

**Storage & Handling:**

Store containers in sheltered area. Use approved equipment for transport to avoid rupturing container.

**Spillage:**

Confine to area of spill. Solidify and dispose of in an approved sanitary landfill according to local regulations. This product does not meet the definition of hazardous waste as defined under 40 CFR 261.

**First Aid:**

**Skin:** Wash off skin with soap and water.  
**Eyes:** Flush eyes immediately with large amounts of water for at least 15 minutes.  
**Inhalation:** Can cause headache, nausea, irritation of nose, throat and lungs. Move to fresh air.  
**Ingestion:** Treat symptomatically and contact a doctor.

**Non-Flammable**

**For more information,**  
refer to the material safety data sheet.

BrewPro, Inc.  
9483 Reading Road  
Cincinnati, OH 45215  
513-577-7200

brewerproducts.com