

1. PRODUCT NAME
Asphalt-Tac™
2. DISTRIBUTOR

BREWPRO INC
Phone: 513-577-7200
Fax: 513-577-7210
Email: info@Brewpro.net
Website: www.Brewpro.net

3. PRODUCT DESCRIPTION

Asphalt-Tac is an asphalt emulsion that meets DOT standards for SS-1h.

- **Good Adhesion:** A penetrating surfactant package insures bonding to the surface.
- **Fast Setting:** Less waiting time required before sealcoating.
- **Ready to Use:** A convenient, fast and easy one-component product.

4. INSTALLATION**Preparatory Work:**

Surface should be dry, clean and free of all loose material, dirt and dust.

Methods:

May be used directly from pour pot or suitable mechanized equipment.

Mix Design:

For priming patches, do not dilute, use full strength. Mix well before use. As a wash coat on pavement surfaces, cut with at least 5 parts water to 1 part Asphalt-Tac.

Application:

As a tack prior to asphalt overlays or under patches, apply .1 gal./sq Asphalt-Tac to the prepared surface.

Precautions:

Keep out of reach of children. Container should be closed when not in use. Contains petroleum distillate. Avoid breathing vapor or prolonged contact with skin or eyes. Flush immediately with water. Consult Neyra material safety data sheet before use.

5. MAINTENANCE

Tools and equipment may be cleaned promptly with water.

6. TECHNICAL DATA**Environmental Considerations:**

Asphalt-Tac is considered non-hazardous when tested according to the EPA's TCLP. Asphalt-Tac is a water-based material containing less than 10g/L (.08 lbs./gal.) VOC content.

Physical Composition:

As supplied, Asphalt-Tac meets ASTM D977, Standard Specification for Emulsified Asphalts.

Drying Time:

Varies with weather conditions.

Non-Flammability:

The cured product shows no tendency to flash or ignite.

7. TECHNICAL SERVICE

Material safety data sheets, product and application recommendations, as well as assistance with special situations and field service are available upon request.

8. WARRANTY

The above specifications on product usage are believed to be true and accurate. Manufacturer guarantees that all materials manufactured comply with quality standards as described in the product data sheets. Because the application, handling, weather, workman-ship and equipment are beyond the control of this manufacturer, only the quality of the products as shipped is guaranteed. In no case will the liability of the manufacturer exceed the purchase price of the shipped materials.

9. ADDITIONAL INFORMATION

Brewpro Inc. offers a full line of asphalt pavement maintenance products as well as application equipment. Contact us at 513-577-7200 or info@Brewpro.net

**Packaging:**

Available in 5 gal. pails and 55 gal. steel drums.

Color:

Asphalt-Tac dries black.

Basic Uses:

Asphalt-Tac is designed for priming asphalt or concrete prior to asphalt overlay. It can also be used for priming prior to installing patches.

Composition:

As shipped, Asphalt-Tac is an asphalt emulsion (SS-1h).

Limitations:

Do not allow to freeze. Do not store in direct sunlight or where temperature exceeds 120°F.